

Control No.GB-VGS-02Date FirstMay 16, 2008

Date Revised January 2024

MSDS Number : AA2158-000000022

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

- A. PRODUCT NAME : VGS Series
- B. RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE
 - : Electric Storage Battery.
- C. MANUFACTURER/SUPPLIER/DISTRIBUTOR INFORMATION
 - MANUFACTURER : Sebang Global Battery CO.,Ltd.

122, Jeongdong-ro, Changwon-si, Gyeongsangnam-do

TEL: +82-55-279-9734 FAX: +82-55-282-2658

2. HAZARDS IDENTIFICATION

A. HAZARD CLASSIFICATION

PHYSICAL HAZARDS

: Not Classified.

HEALTH HAZARDS

:	Acute toxicity	Category 4 (inhalation)
:	Skin corrosion/irritation	Category 1
:	Serious eye damage/eye irritation	Category 1
:	Carcinogenicity	Category 1B
:	Germ cell mutagenicity	Category 2
:	Specific target organ toxicity - single exposure	Category 1
:	Specific target organ toxicity - repeated exposur	e Category 1

ENVIRONMENTAL HAZARDS

: Not Classified.

B. GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAMS



SIGNAL WORD : DANGER.

HAZARD STATEMENTS

- H332 Harmful if inhaled.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H350 May cause cancer (inhalation).
- H341 Suspected of causing genetic defects.
- H370 Specific target organ toxicity single exposure; Respiratory tract irritation



Control No.GB-VGS-02Date FirstMay 16, 2008Date RevisedJanuary 2024

MSDS Number : AA2158-000000022

	H372	Causes damage to organs (Hematopoietic system, kidney, central nervous system, peripheral nervous system, cardiovascular system, immune system, respiratory).
	H362	May cause harm to breast-fed children
	PRECAUTIONARY STA	TEMENTS :
	[Prevention]	
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P271	Use only outdoors or in a wellventilated area.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P264	Wash hands thoroughly after handling.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P281	Use personal protective equipment as required.
	P270	Do not eat, drink or smoke when using this product.
	[Response]	
	P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P312	Call a POISON CENTER or doctor/physician if you feel unwell.
	P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
	P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P363	Wash contaminated clothing before reuse.
	P310	Immediately call a POISON CENTER or doctor/physician.
	P321	Specific treatment (see on this label).
	P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P308 + P313	IF exposed or concerned: Get medical advice/attention.
	P307+P311	IF exposed: Call a POISON CENTER or doctor/physician.
	P314	Get medical advice/attention if you feel unwell.
	[Storage]	
	P405	Store locked up.
	[Disposal]	
	P501	Dispose of contents/container in accordance with local/regional/national regulations.
C.	OTHER HAZARDS WH	ICH DO NOT RESULT IN CLASSIFICATION (e.g. Dust explosion hazards)
	NFPA/HMIS Rating	
		Health=3, Flammability=0, Instability=1

(0 = Insignificant 1 = Slight 2 = Moderate 3 = High 4 = Extreme)



Material Safety Data sheet (MSDS)

Control No.GB-VGS-02Date FirstMay 16, 2008Date RevisedJanuary 2024

MSDS Number : AA2158-000000022

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name / Synonym	CAS No. or ID	Content (%)
Lead	7439-92-1 / 231-100-4*	64
Electrolyte (sulfuric acid / water / solution)	7664-93-9 / 231-639-5*	13 - 17
Phosphoric acid	7664-38-2 / 231-633-2*	3 - 4
Butadiene-Acrylonitrile-Styrene copolymer / ABS Resin	9003-56-9 / exempted	7 - 10
Silica, amorphous, fumed, crystfree	112945-52-5 / included	7 - 10
Separator	Not available	7 - 10

* European Inventory of Existing Commercial Chemical Substances (EINECS).

4. FIRST AID MEASURES

A. EYE CONTACT	:	If a battery ruptures, do not rub or scratch exposed eye. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. GET MEDICAL ATTENTION IMMEDIATELY.
B. SKIN CONTACT	:	If a battery ruptures, do not rub or scratch exposed skin. If liquid get on the skin, immediately flush the contaminated skin with water for at least 15 minutes. If liquid penetrate through the clothing, immediately remove the clothing and shoes under a safety shower and continue to wash the skin for at least 15 minutes. GET MEDICAL ATTENTION IMMEDIATELY.
C. INHALATION	:	If a battery ruptures, move to fresh air in case of accidental inhalation of mist. If breathing has stopped, perform artificial respiration. If breathing is difficult, give oxygen. GET MEDICAL ATTENTION AS SOON AS POSSIBLE.
D. INGESTION	:	If solutions of a battery chemicals have been swallowed and the person is conscious, give one glass of water. Vomiting may occur spontaneously, but Do NOT induce vomiting. Never give anything by mouth to an unconscious person. GET MEDICAL ATTENTION IMMEDIATELY.
E. MOST IMPORTANT	SYN	IPTOMS/EFFECTS, ACUTE OR DELAYED
EYES	:	Not a likely route of exposure. If a battery ruptures, direct contact with the liquid or exposure to vapors or mists may cause tearing, redness, swelling, corneal damage and irreversible eye damage. Splashes in the eyes will cause severe burns.
SKIN	SKIN :	Not a likely route of exposure. Direct contact with internal components of a battery can be severely irritating to the skin and may result in redness, swelling, burns and severe skin damage. Skin contact may aggravate an existing dermatitis condition.
INHALATION	:	Not a likely route of exposure. If a battery ruptures, may be harmful or fatal if inhaled in a confined area. May cause severe irritation and burns of the nose, throat and respiratory tract.
INGESTION	:	Not a likely route of exposure. Causes serious burns of the mouth or perforation of the esophagus or stomach. May be fatal if swallowed.



Control No. May 16, 2008 Date First Date Revised January 2024

GB-VGS-02

MSDS Number : AA2158-000000022

* Lead may causes toxic to blood, kidneys, central nervous system (CNS). Repeated or prolonged exposure to lead can produce target organs damage.

- F. INDICATION OF IMMEDIATE MEDICAL ATTENTION AND NOTES FOR PHYSICIAN
 - Based on the individual reactions of the patient, the physician's judgement should be used to control symptoms and clinical condition.

5. FIRE FIGHTING MEASURES

- A. SUITABLE (AND UNSUITABLE) EXTINGUISHING MEDIA
 - Use extinguishing media appropriate for surrounding fire.
 - If a battery ruptures, use dry chemical, soda ash, lime, sand or carbon dioxide.
- **B. SPECIFIC HAZARDS ARISING FROM THE CHEMICAL**
 - Lead, lead compounds and sulfuric acid fume may be released during a fire involving the product.
- C. SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS
 - Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing.
- D. FIRE AND EXPLOSION HAZARD
 - Not flammable.
 - Battery may rupture due to pressure buildup when exposed to excessive heat and may be result in the release of corrosive materials.

6. ACCIDENTAL RELEASE MEASURES

- A. NECESSARY MEASURES AND PROTECTIVE GEAR TO PROTECT HUMANS
 - If a battery ruptures, avoid contact with skin, eves and clothing. Do not touch spilled material. Use personal protective equipment recommended in Section 8 (Exposure Controls/Personal Protection).
- **B. NECESSARY MEASURES TO PROTECT ENVIRONMENT**

:

- Notify authorities and appropriate federal, state, and local agencies. Prevent the product from spreading into the environment. Avoid direct discharge into drains.
- C. METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP
 - SMALL SPILLS: Collect all released material in a plastic lined metal container. If necessary neutralize the residue with a dilute solution of sodium carbonate. Wash affected area.
 - LARGE SPILLS: Contain liquid using absorbent material, by digging trenches or by building a dike. Absorb with dry earth, sand or other non-combustible
 - material. Neutralize the residue with a dilute solution of sodium carbonate. Dispose of all contaminated materials in accordance with current local regulations.

7. HANDLING AND STORAGE



Control No.	GB-VGS-02		
Date First	May 16, 2008		
Date Revised	January 2024		

MSDS Number : AA2158-000000022

A. PRECAUTIONS FOR SAFE HANDLING

- : Protect from physical damage.
- B. CONDITIONS FOR SAFE STORAGE (INCLUDING ANY INCOMPATIBILITIES)
 - Avoid contact with eyes. Store in a cool, dry, ventilated area away from sources
 of heat, moisture, incompatibilities, and direct sunlight. Have emergency equipment (for fires, spills, leaks, etc.) readily available.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- A. OCCUPATIONAL EXPOSURE LIMIT(S), BIOLOGICAL EXPOSURE STANDARD
 - OSHA-PEL 0.05 mg/m3 (Lead), 1 mg/m3 (Sulfuric acid), 1 mg/m3 (Phosphoric acid), 0.1 mg/m3 (Silica (amorphous silica, fused) (respirable dust))
 - ACGIH-TLV TWA 0.05 mg/m3 (Lead), TWA 0.2 mg/m3 (Sulfuric acid), TWA 1 mg/m3, STEL 3 mg/m3 (Phosphoric acid), TWA 0.1 mg/m3 (Silica (amorphous silica, fused) (respirable dust))

B. APPROPRIATE ENGINEERING CONTROLS

: Use local exhaust ventilation if necessary to control airborne mist and vapor.

C. INDIVIDUAL PROTECTION MEASURES

Respiratory protection :	If significant mists or aerosols are generated an approved respirator is recommended. If respiratory protection is required, institute a complete respiratory protection program including selection, fit testing, training, maintenance and inspection.				
Eye protection :	Wear safety glasses with side shields (or goggles).				
Hand protection :	Wear chemical resistant gloves. Gloves should be replaced immediately if signs of degradation are observed.				
Body protection :	Use good work and personal hygiene practices to avoid exposure. Consider the provision in the work area of a safety shower and eyewash. Always wash thoroughly after handling chemicals.				

9. PHYSICAL AND CHEMICAL PROPERTIES

A. APPEARANCE (PHYSICAL STATE, COLOUR etc.	.) :	Off-white cloudy liquid with solid object.
B. Odour : Characteristics.		
C. ODOR THRESHOLD : Not available.		
D. pH : pH < 1 (Sulfuric acid)		
E. MELTING POINT/FREEZING POINT	:	Not available.
F. INITIAL BOILING POINT AND BOILING RANGE	:	Not available.
G. FLASH POINT : Non-flammable.		
H. EVAPORATION RATE	:	Not available.

			Control No.	GB-VGS-02
SEBANG	Material Safety Data	a sheet (MSDS)	Date First	May 16, 2008
			Date Revised	January 2024
		MSDS Number	: AA2158-0	00000022
I. FLAMMABILITY (SOL	.ID, GAS)	: Not applicable.		
J. UPPER/LOWER FLA	MMABILITY OR EXPLOSIVE LI	MITS		
	: Non-flammable.			
K. VAPOR PRESSURE	: Not available.			
L. SOLUBILITY	: Soluble in water.			
M. VAPOR DENSITY	: Not available.			
N. SPECIFIC GRAVITY	: Not available.			
O. PARTITION COEFFIC	CIENT OF n-OCTANOL/WATE	: Not available.		
P. AUTO-IGNITION TEM	IPERATURE	: Not applicable.		
Q. DECOMPOSITION TE	EMPERATURE	: Not available.		
R. VISCOSITY	: Not available.			
S. MOLECULAR WEIGH	IT	: Mixture.		

10. STABILITY AND REACTIVITY

- A. CHEMICAL STABILIT: Stable at normal temperatures and storage conditions.
- B. POSSIBILITY OF HAZARDOUS REACTIONS

: Hazardous polymerization will not occur.

- C. CONDITIONS TO AVOID (STATIC DISCHARGE, SHOCK, VIBRATION etc.):
 - Overcharging. Sources of ignition. Mechanical impact. Contact with incompatible chemicals.

D. SUBSTANCES TO AVOID

: If a battery ruptures, avoid contact with organic materials and alkaline materials.

E. HAZARDOUS DECOMPOSITION PRODUCTS

Lead, Lead compounds and sulfuric acid fumes may be released during a fire involving the product.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

Inhalation		Corrosive. severe irritation and burns.			
Ingestion		Serious burns.			
Eye/Skin					
Eye	:	Tearing, redness, swelling, corneal damage, irreversible eye damage and severe burns.			
Skin	:	Redness, swelling, burns and severe skin damage.			

B. Delayed and immediate effects and also chronic effects from short and long term exposure Acute toxicity (possible route of exposure) :

		Material Safety Data sheet (MSDS			Control No.	GB-VGS-02
SEBANG	N			neet (MSDS)	Date First	May 16, 2008
					Date Revised	January 2024
				MSDS Number	: AA2158-0	000000022
Oral (LD50)	:	Rat) mg/kg (Sulfuric ac) mg/kg (Phosphoric		
Skin (LD50)	:	Rabbit	2740)mg/kg (Phosphoric	acid)	
Inhalation (LC50)	:	Rat	0.09	4 mg/L(4hr) (dust//n	nist)	
Skin corrosion/irritatior	n		:	cat 1		
Serious eye damage/ir	rritat	tion	:	cat 1		
Respiratory sensitization	on		:	Not available.		
Skin sensitization	:	Not available.				
Carcinogenicity	:	cat 1B				
		ACGIH Group A2, IARC G * Note: Sulfuric acid mist is ACGIH Group A3, IARC G	not e	expected under norr	nal use of the	•
Germ cell mutagenicity	y		:	cat 2		
Reproductive toxicity	:	Not available.				
STOST-single exposu	ire		:	cat 1		
	:	Respiratory.				
STOST-repeated expo	osur	e	:	cat 1		
	•	Hematopoietic system, kidi system, cardiovascular sys				l nervous
Aspiration hazard	:	Not available.				
C. Numeric measure of to	oxici	ity (such as acute toxicity e	stima	tes) - ATEmix		
Oral (LD50)	:	Rat	> 5,0)00 mg/kg		
Skin (LD50)	:	Rabbit	> 5,0)00 mg/kg		
Inhalation (LC50)	:	Rat	2.51	mg/L(4hr) (dust//mi	ist)	

12. ECOLOGICAL INFORMATION

- A. Aquatic/terrestrial ecology toxicity
 - Fish (LC50):Not available.Daphnia (EC50):Not available.
 - Algae (EC50) : Not available.
- B. Persistence and degradability
 - Persistence : Not available.
 - Degradability : Not available.
- C. Bioaccumulative potential
- : Not available.
- D. Mobility in soil : Not available.
- E. Other hazardous effects

Not available.

:



Control No.GB-VGS-02Date FirstMay 16, 2008Date RevisedJanuary 2024

MSDS Number : AA2158-000000022

13. DISPOSAL CONSIDERATIONS

A. DISPOSAL METHODS

Dispose of in accordance with local, state, and federal regulations. Hazardous wastes must be transported by a licensed hazardous waste transporter and

: disposed of or treated in a properly licensed hazardous waste treatment, storage, disposal or recycling facility. Consult local, state, and federal regulations for specific requirements.

B. PRECAUTIONS (INCLUDING DISPOSAL OF CONTAMINATED CONTAINER OR PACKAGE)

Since emptied containers retain product residue, follow label warnings even after container is emptied.

14. TRANSPORT INFORMATION

All Global's VGS series are valve regulated lead acid (VRLA) batteries. GLOBAL's VRLA batteries meet test specifications for "non-spillable electric storage batteries", as required by D.O.T., 49 CFR 173. 159(d), and IMO/IMDG, and ICAO/IATA packing instruction 872 and note A67; therefore, are non-regulated when protected against short circuits, kept upright, and securely packaged. The battery and the outer packaging must be plainly and durably marked "NONSPILLABLE BATTERY" or "NONSPILLABLE".

These batteries meet the requirements contained in the following special provisions.

A. Regulatory Body	Special provisions			
B. U. S. DOT	Unregulated, meets the requirement of 49 CFR 173.159(d)			
C. IATA / ICAO	Unregulated, meets the requirements of Special Revisions A67			
d. Imo Imdg	Unregulated, meets the requirements of Special Revisions #238			
E. UN Number	2800			

* Proper Shipping Name : Batteries, wet, non-spillable

15. REGULATORY INFORMATION

■ INVENTORIES	
EINECS/EU :	Listed (EINECS No. 231-100-4, 231-639-5, 231-633-2)
TSCA/US :	Listed.
ENCS/JAPAN:	Listed (ENCS No. 1-527, 1-430, 1-422, 6-176)
AICS/AUSTRALIA :	Listed.
DSL/CANADA :	Listed.
IECSC/CHINA:	Listed.
PICCS/PHILIPPINES :	Listed.
KECI/S.KOREA :	Listed (KE-21887, KE-32570, KE-27427, KE-29398, KE-30953)
■ International Environme	ntal Agreement
PIC :	Not listed.
POPs :	Not listed.

1		1	
		Control No.	GB-VGS-02
SEBANG	Material Safety Data sheet (MSDS)	Date First	May 16, 2008
		Date Revised	January 2024
	MSDS Number	: AA2158-0	000000022
Ozone depletion	: Not listed.		
EU. Directive 67/548/E	EC on the classification, packaging, and labelling of dang	jerous substan	ces, Annex I
Classification	: C; R35		
Risk Phrases	: R35		
Safety Phrases	: S1/2, S26, S30, S45		
₪ U.S. Federal, Heanth	and Environment) and U.S. Federal, Right-To-Know	W	
CERCLA Section 103	(40 CFR 302.4)		
	: 10lb (4.535 kg) (Lead), 1000 lb (453.599 kg) (Si (2267.995 kg) (Phosphoric acid)	ulfuric acid),	5000 lb
EPCRA (SARA Title II	I) Section 302 (EHS -TPQ)		
	: 1000 lb (453.599 kg) (Sulfuric acid)		
EPCRA (SARA Title II	I) Section 304 (EHS - Reporting Quantities)		
	: 1000 lb (453.599 kg) (Sulfuric acid)		
EPCRA (SARA Title II	l) Section 313 - Toxic chemical release reporting		
	: Sulfuric acid (acid aerosols including mists, vap airborne forms of any particle size)	ors, gas, fog	, and other
OSHA Specifically Re	egulated Substances (29 CFR 1910.10011052)		

: Not applicable.

□ CANADA REGULATORY INFORMATION

WHMIS Ingredient Disclosure List : Regulated.

NOTE: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the Safety Data Sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

A. SOURCE OF DATA :

Guideline for Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

EC-ECB, International Uniform Chemical Information Database (IUCLID)

Hazardous Substances Data Bank (HSDB)

Registry of Toxic Effects of Chemical Substances (RTECS)

National Institute of Technology and Evaluatio -NITE (Japan).

NFPA 704 Standard System for the Identification of the Hazards of Materials for Emergency Response.

International Chemical Safety Cards(ICSC)(http://www.nihs.go.jp/ICSC) **3E Company/Ariel WebInsight DB**.

B. THE DATE OF PREPARATION OF THE MSDS : May 16, 2008

C. THE DATE OF PREPARATION OF THE LATEST REVISION

: January 2024

D. OTHER INFORMATIO:

SEBANG	Material Safety Data sheet (MSDS)	Control No.	GB-VGS-02
		Date First	May 16, 2008
		Date Revised	January 2024

MSDS Number : AA2158-000000022

The above information is believed to be correct but does not propose to be all inclusive and shall be used only as a guide. Sebang Global Battery CO.,Ltd. shall not be held liable for any damage resulting from handling or from contact with the above product. Each individual should make a determination as to the suitability of the information for their particular purpose(s). Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.