

# Material Safety Data sheet (MSDS)

Control No.GB-PSHS-04Date FirstMay 16, 2008

 Date Revised
 January 2024

 MSDS Number : AA2158-0000000020

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

- A. PRODUCT NAME : PS/HS Battery Series
- B. RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE

: Electric Storage Battery.

- C. MANUFACTURER/SUPPLIER/DISTRIBUTOR INFORMATION
  - MANUFACTURER : Sebang Global Battery CO.,Ltd.

122, Jeongdong-ro, Changwon-si, Gyeongsangnam-do

TEL: +82-55-279-9734 FAX: +82-55-282-2658

## 2. HAZARDS IDENTIFICATION

## A. HAZARD CLASSIFICATION

## PHYSICAL HAZARDS

: Not Classified.

## HEALTH HAZARDS

:	Acute toxicity	Category 4 (inhalation)
:	Skin corrosion/irritation	Category 1
:	Serious eye damage/eye irritation	Category 1
:	Carcinogenicity	Category 1B
:	Germ cell mutagenicity	Category 2
:	Specific target organ toxicity - single exposure	Category 1
:	Specific target organ toxicity - repeated exposure	Category 1
:	Hazardous to the aquatic environment - Acute H	¿Category 1
:	Hazardous to the aquatic environment - Chronic	Category 1

# ENVIRONMENTAL HAZARDS

: Not Classified.

# B. GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAMS



SIGNAL WORD : DANGER.

HAZARD STATEMENTS

- H332 Harmful if inhaled.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.

		Control No.	GB-PSHS-04				
SEBANG	Material Safety Data sheet (MSDS)	Date First	May 16, 2008				
	•	Date Revised	January 2024				
	MSDS Number	: AA2158-00	00000020				
H350	May cause cancer (inhalation).						
H341	Suspected of causing genetic defects.						
H370	Specific target organ toxicity – single exposure; Re	spiratory tract	irritation				
L1270	Causes damage to organs (Hematopoietic system, kidney, central nervous system, peripheral nervous system, cardiovascular system, immune system, respiratory).						
H372							
H400	Very toxic to aquatic life						
H410	Very toxic to aquatic life with long lasting effects						
H362	May cause harm to breast-fed children						
PRECAUTIONARY ST	ATEMENTS :						
[Prevention]							
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.						
P271	Use only outdoors or in a wellventilated area.						
P260	Do not breathe dust/fume/gas/mist/vapours/spray.						
P264	Wash hands thoroughly after handling.						
P280	Wear protective gloves/protective clothing/eye protective	ection/face pro	tection.				
P201	Obtain special instructions before use.						
P202	Do not handle until all safety precautions have been read and understood.						
P281	Use personal protective equipment as required.						
P270	Do not eat, drink or smoke when using this product						
[Response]							
P304 + P340	IF INHALED: Remove victim to fresh air and keep a comfortable for breathing.	at rest in a pos	ition				
P312	Call a POISON CENTER or doctor/physician if you	feel unwell.					
P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vol	miting.					
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediatel Rinse skin with water/shower.	y all contamina	ated clothing.				
P363	Wash contaminated clothing before reuse.						
P310	Immediately call a POISON CENTER or doctor/phy	sician.					
P321	Specific treatment (see on this label).						
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several lenses, if present and easy to do. Continue rinsing.	minutes. Rem	ove contact				
P308 + P313	IF exposed or concerned: Get medical advice/atten	tion.					
P307+P311	IF exposed: Call a POISON CENTER or doctor/phy						
P314	Get medical advice/attention if you feel unwell.						
[Storage]							
P405	Store locked up.						
[Disposal]							
P501	Dispose of contents/container in accordance with lo regulations.	ocal/regional/n	ational				

C. OTHER HAZARDS WHICH DO NOT RESULT IN CLASSIFICATION (e.g. Dust explosion hazards) NFPA/HMIS Rating



Material Safety Data sheet (MSDS)

Date FirstMay 16, 2008Date RevisedJanuary 2024

GB-PSHS-04

## MSDS Number : AA2158-000000020

Control No.

Health=3, Flammability=0, Instability=1

(0 = Insignificant 1 = Slight 2 = Moderate 3 = High 4 = Extreme)

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

1

Chemical name / Synonym	<u>CAS No</u>	Content (%)
Lead	7439-92-1	68 - 70
Antimony	7440-36-0	< 1.4
Electrolyte (sulfuric acid / water / solution)	7664-93-9	28 - 30
Butadiene-Acrylonitrile-Styrene copolymer / ABS Resin	9003-56-9	1 - 2
Acrylonitrile-Styrene copolymer / AS Resin	9003-54-7	4 - 5
Separator	Not available	2 - 3

\* European Inventory of Existing Commercial Chemical Substances (EINECS).

#### 4. FIRST AID MEASURES

A. EYE CONTACT	:	If a battery ruptures, do not rub or scratch exposed eye. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. GET MEDICAL ATTENTION IMMEDIATELY.
B. SKIN CONTACT	:	If a battery ruptures, do not rub or scratch exposed skin. If liquid get on the skin, immediately flush the contaminated skin with water for at least 15 minutes. If liquid penetrate through the clothing, immediately remove the clothing and shoes under a safety shower and continue to wash the skin for at least 15 minutes. GET MEDICAL ATTENTION IMMEDIATELY.
C. INHALATION	:	If a battery ruptures, move to fresh air in case of accidental inhalation of mist. If breathing has stopped, perform artificial respiration. If breathing is difficult, give oxygen. GET MEDICAL ATTENTION AS SOON AS POSSIBLE.
D. INGESTION	:	If solutions of a battery chemicals have been swallowed and the person is conscious, give one glass of water. Vomiting may occur spontaneously, but Do NOT induce vomiting. Never give anything by mouth to an unconscious person. GET MEDICAL ATTENTION IMMEDIATELY.
E. MOST IMPORTANT	SYN	IPTOMS/EFFECTS, ACUTE OR DELAYED
EYES	:	Not a likely route of exposure. If a battery ruptures, direct contact with the liquid or exposure to vapors or mists may cause tearing, redness, swelling, corneal damage and irreversible eye damage. Splashes in the eyes will cause severe burns.
SKIN	:	Not a likely route of exposure. Direct contact with internal components of a battery can be severely irritating to the skin and may result in redness, swelling, burns and severe skin damage. Skin contact may aggravate an existing dermatitis condition.
INHALATION	:	Not a likely route of exposure. If a battery ruptures, may be harmful or fatal if inhaled in a confined area. May cause severe irritation and burns of the nose, throat and respiratory tract.

EE		Control No.	GB-PSHS-04		
SEBANG	Material Safety Data sheet (MSDS)	Date First	May 16, 2008		
		Date Revised	January 2024		

# MSDS Number : AA2158-000000020

INGESTION : Not a likely route of exposure. Causes serious burns of the mouth or perforation of the esophagus or stomach. May be fatal if swallowed.

\* Lead may causes toxic to blood, kidneys, central nervous system (CNS). Repeated or prolonged exposure to lead can produce target organs damage.

- F. INDICATION OF IMMEDIATE MEDICAL ATTENTION AND NOTES FOR PHYSICIAN
  - Based on the individual reactions of the patient, the physician's judgement should be used to control symptoms and clinical condition.

#### **5. FIRE FIGHTING MEASURES**

A. SUITABLE (AND UNSUITABLE) EXTINGUISHING MEDIA

- Use extinguishing media appropriate for surrounding fire.
- If a battery ruptures, use dry chemical, soda ash, lime, sand or carbon dioxide.
- B. SPECIFIC HAZARDS ARISING FROM THE CHEMICAL
  - Lead, lead compounds and sulfuric acid fume may be released during a fire involving the product.
- C. SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS
  - Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing.
- D. FIRE AND EXPLOSION HAZARD

Not flammable.

: Battery may rupture due to pressure buildup when exposed to excessive heat and may be result in the release of corrosive materials.

#### 6. ACCIDENTAL RELEASE MEASURES

## A. NECESSARY MEASURES AND PROTECTIVE GEAR TO PROTECT HUMANS

If a battery ruptures, avoid contact with skin, eyes and clothing. Do not touch spilled material. Use personal protective equipment recommended in Section 8 (Exposure Controls/Personal Protection).

## B. NECESSARY MEASURES TO PROTECT ENVIRONMENT

Notify authorities and appropriate federal, state, and local agencies. Prevent the product from spreading into the environment. Avoid direct discharge into drains.

## C. METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP



ontrol No.	GB-PSHS-04
ate First	May 16, 2008
ate Revised	January 2024

# MSDS Number : AA2158-000000020

SMALL SPILLS: Collect all released material in a plastic lined metal container. If necessary, Neutralize the residue with a dilute solution of alkali(soda ash, sodium carbonate, lime, etc). Wash affected area.

LARGE SPILLS: Contain liquid using absorbent material, by digging trenches or by building a dike. Absorb with dry earth, sand or other non-combustible material. If necessary, Neutralize the residue with a dilute solution of alkali(soda ash, sodium carbonate, lime, etc). Dispose of all contaminated materials in accordance with current local regulations.

## 7. HANDLING AND STORAGE

## A. PRECAUTIONS FOR SAFE HANDLING

- : Protect from physical damage.
- B. CONDITIONS FOR SAFE STORAGE (INCLUDING ANY INCOMPATIBILITIES)
  - Avoid contact with eyes. Store in a cool, dry, ventilated area away from sources
  - : of heat, moisture, incompatibilities, and direct sunlight. Have emergency equipment (for fires, spills, leaks, etc.) readily available.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. OCCUPATIONAL EXPOSURE LIMIT(S), BIOLOGICAL EXPOSURE STANDARD

OSHA-PEL	0.05 mg/m3 (Lead), 1 mg/m3 (Sulfuric acid), 0.5 mg/m3 (Antimony)
ACGIH-TLV	TWA 0.05 mg/m3 (Lead), TWA 0.2 mg/m3 (Sulfuric acid) TWA 0.5 mg/m3(Antimony)

## **B. APPROPRIATE ENGINEERING CONTROLS**

: Use local exhaust ventilation if necessary to control airborne mist and vapor.

## C. INDIVIDUAL PROTECTION MEASURES

Respiratory protection :	If significant mists or aerosols are generated an approved respirator is recommended.
Eye protection :	Wear safety glasses with side shields (or goggles).
Hand protection :	Wear chemical resistant gloves. Gloves should be replaced immediately if signs of degradation are observed.
Body protection :	Use good work and personal hygiene practices to avoid exposure. Consider the provision in the work area of a safety shower and eyewash. Always wash thoroughly after handling chemicals.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

A. APPEARANCE (PHYSICAL STATE, COLOUR etc.) : Off-white cloudy liquid with solid object.

B. Odour : Characteristics.

SFaur	Motorial Oafst, D.			Control No.	GB-PSHS-04
SEBANG	Material Safety Dat	a sr	ieet (MSDS)	Date First	May 16, 2008
			MSDS Number	Date Revised	January 2024
C. ODOR THRESHOLD	· Not available			. AAZ 130-00	00000020
D. pH	: pH < 1 (Sulfuric acid)				
E. MELTING POINT/FR	,		Not available.		
	NT AND BOILING RANGE	•	Not available.		
G. FLASH POINT		•	Not available.		
H. EVAPORATION RAT			Not available.		
		•			
	MMABILITY OR EXPLOSIVE I	IN/IT	Not applicable.		
J. UPPER/LOWER FLA	: Non-flammable.		5		
L. SOLUBILITY					
M. VAPOR DENSITY					
N. SPECIFIC GRAVITY			N1. 6		
	CIENT OF n-OCTANOL/WATE	:1:	Not available.		
P. AUTO-IGNITION TEN		:	Not applicable.		
Q. DECOMPOSITION TE		:	Not available.		
R. VISCOSITY					
S. MOLECULAR WEIGH		:	Mixture.		
	perties are typical values for t				
	SICAL STATE, COLOUR etc.)	:	Bluish white, silve	ry gray.	
B. Odour	: None.				
C. ODOR THRESHOLD	: Not available.				
D. pH	: Not applicable.				
E. MELTING POINT/FRE	EEZING POINT	:	<b>327</b> .5℃		
F. INITIAL BOILING POI	NT AND BOILING RANGE	:	1740℃ (1013 hPa	ı)	
G. FLASH POINT	: Non-flammable.				
H. EVAPORATION RAT	E	:	Not applicable.		
I. FLAMMABILITY (SOL	.ID, GAS)	:	Not applicable.		
J. UPPER/LOWER FLA	MMABILITY OR EXPLOSIVE I		6		
	: Non-flammable.				
K. VAPOR PRESSURE	: 1.33 hPa (973℃)				
L. SOLUBILITY	: Insoluble in water.				
M. VAPOR DENSITY	: Not applicable.				
N. SPECIFIC GRAVITY	: 11.34 g/cm3				
O. PARTITION COEFFIC	CIENT OF n-OCTANOL/WATE	EF :	Not applicable.		
P. AUTO-IGNITION TEN	IPERATURE	:	Not applicable.		
Q. DECOMPOSITION T	EMPERATURE	:	Not applicable.		
R. VISCOSITY	: Not applicable.				
S. MOLECULAR WEIGH	IT	:	207.2		

	Material Safety Data sheet (MSDS) Date First May 16, 2008	GB-PSHS-04	
SEBANG	Material Safety Data sheet (MSDS)	<b>DS)</b> Date First May 16, 2008	
		Date Revised	January 2024

## MSDS Number : AA2158-000000020

Note: These physical properties are typical values for Lead(Pb).

#### **10. STABILITY AND REACTIVITY**

- A. CHEMICAL STABILIT: Stable at normal temperatures and storage conditions.
- **B. POSSIBILITY OF HAZARDOUS REACTIONS** 
  - : Hazardous polymerization will not occur.
- C. CONDITIONS TO AVOID (STATIC DISCHARGE, SHOCK, VIBRATION etc.):
  - Overcharging. Sources of ignition. Mechanical impact. Contact with incompatible chemicals.

#### D. SUBSTANCES TO AVOID

- : If a battery ruptures, avoid contact with organic materials and alkaline materials.
- E. HAZARDOUS DECOMPOSITION PRODUCTS
  - Lead, Lead compounds and sulfuric acid fumes may be released during a fire involving the product.

## **11. TOXICOLOGICAL INFORMATION**

A. Information on the like	ely	routes of exposure		
Inhalation	:	Corrosive. severe irritatior	n and	burns.
Ingestion	:	Serious burns.		
Eye/Skin				
Eye	:	Tearing, redness, swelling severe burns.	, cor	neal damage, irreversible eye damage and
Skin	:	Redness, swelling, burns	and s	evere skin damage.
B. Delayed and immedia	ate	effects and also chronic effe	ects f	rom short and long term exposure
Acute toxicity (possib	le r	oute of exposure)	:	
Oral (LD50):		Rat	2140 mg/kg (Sulfuric acid), 7000 mg/kg (Antimony)	
Skin (LD50)	):	Not available.		
Inhalation (LC50)	):	Rat	0.0	94 mg/L(4hr) (dust//mist)
Skin corrosion/irritatio	on		:	cat 1
Serious eye damage/	'irrit	ation	:	cat 1
Respiratory sensitizat	tion		:	Not available.
Skin sensitization	:	Not available.		
Carcinogenicity	:	cat 1B		
		* Note: Sulfuric acid mist i	s not	1 (Mist containing sulfuric acid) expected under normal use of the product. 2B (Lead), IARC Group 3 (ABS, AS Resin)

~~					Control No.	GB-PSHS-04
SEBANG		Material Safety Data sheet (MSDS)		Date First	May 16, 2008	
			Date Revised	January 2024		
				MSDS Number	: AA2158-00	00000020
Germ cell mutagenicit	y		:	cat 2		
Reproductive toxicity	:	Not available.				
STOST-single exposu	ire		:	cat 1		
	:	Respiratory.				
STOST-repeated expo	osu	re	:	cat 1		
	:	Hematopoietic system, kidn system, cardiovascular syst	-			l nervous
Aspiration hazard	:	Not available.				
C. Numeric measure of to	C. Numeric measure of toxicity			tes) - ATEmix		
Oral (LD50)	:	Rat	> 5,0	000 mg/kg		
Skin (LD50)	:	Not available.				
Inhalation (LC50)	:	Rat	2.51	mg/L(4hr) (dust//m	ist)	

## **12. ECOLOGICAL INFORMATION**

A. Aquatic/terrestrial e	ecology toxicity	
Fish (LC50)	: Not available.	
Daphnia (EC50)	: Not available.	
Algae (EC50)	: Not available.	
B. Persistence and de	egradability	
Persistence	: Not available.	
Degradability	: Not available.	
C. Bioaccumulative potential		
	: Not available.	
D. Mobility in soil	: Not available.	
E. Other hazardous effects		: Not available.

## **13. DISPOSAL CONSIDERATIONS**

1

#### A. DISPOSAL METHODS

Dispose of in accordance with local, state, and federal regulations. Hazardous wastes must be transported by a licensed hazardous waste transporter and

: disposed of or treated in a properly licensed hazardous waste treatment, storage, disposal or recycling facility. Consult local, state, and federal regulations for specific requirements.

## B. PRECAUTIONS (INCLUDING DISPOSAL OF CONTAMINATED CONTAINER OR PACKAGE)

Since emptied containers retain product residue, follow label warnings even after container is emptied.



Control No.GB-PSHS-04Date FirstMay 16, 2008Date RevisedJanuary 2024

MSDS Number : AA2158-000000020

#### **14. TRANSPORT INFORMATION**

The information in this section is for reference only and should not take the place of a shipping paper (BL). Please note that the proper Shipping Name / Hazard Class may vary by packaging, properties, and mode of transportation.

- A. UN NUMBER : UN 2794
- B. UN PROPER SHIPPING NAME

#### BATTERIES, WET, FILLED WITH ACID

- C. TRANSPORT HAZARD CLASS(ES):8D. PACKING GROUP (IF APPLICABLE):Not available.
- E. MARINE POLLUTANT SUBSTANCES (APPLICABLE/NOT APPLICABLE)

: Not Applicable.

F. SPECIAL PRECAUTIONS FOR USER : Not available.

## **15. REGULATORY INFORMATION**

#### ■ INVENTORIES

EINECS/EU: Listed (EINECS No. 231-100-4(Lead), 231-639-5(Sulfuric acid)) TSCA/US: Listed. ENCS/JAPAN: Listed (ENCS No. 1-527(Lead), 1-430(Sulfuric acid)) AICS/AUSTRALIA : Listed. DSL/CANADA : Listed. IECSC/CHINA : Listed. PICCS/PHILIPPINES : Listed. KECI/S.KOREA : Listed (KE-21887(Lead), KE-32570(Sulfuric acid)) ■ International Environmental Agreement PIC : Not listed. POPs : Not listed. : Not listed. Ozone depletion EU. Directive 67/548/EEC on the classification, packaging, and labelling of dangerous substances, Annex I Classification : C; R35 Risk Phrases: R35 Safety Phrases : S1/2, S26, S30, S45 ■ U.S. Federal, Heanth and Environment) and U.S. Federal, Right-To-Know CERCLA Section 103 (40 CFR 302.4) : 10lb (4.535 kg) (Lead), 1000 lb (453.599 kg) (Sulfuric acid) EPCRA (SARA Title III) Section 302 (EHS -TPQ) : 1000 lb (453.599 kg) (Sulfuric acid) EPCRA (SARA Title III) Section 304 (EHS - Reporting Quantities) : 1000 lb (453.599 kg) (Sulfuric acid)



Date FirstMay 16, 2008Date RevisedJanuary 2024

GB-PSHS-04

## MSDS Number : AA2158-000000020

Control No.

EPCRA (SARA Title III) Section 313 - Toxic chemical release reporting

: Sulfuric acid (acid aerosols including mists, vapors, gas, fog, and other airborne forms of any particle size)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-.1052)

: Not applicable.

#### ■ CANADA REGULATORY INFORMATION

#### WHMIS Ingredient Disclosure List : Regulated.

NOTE: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the Safety Data Sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

## **16. OTHER INFORMATION**

## A. SOURCE OF DATA :

Guideline for Globally Harmonized System of Classification and Labelling of Chemicals (GHS).

EC-ECB, International Uniform Chemical Information Database (IUCLID)

Hazardous Substances Data Bank (HSDB)

÷

Registry of Toxic Effects of Chemical Substances (RTECS)

National Institute of Technology and Evaluatio -NITE (Japan).

NFPA 704 Standard System for the Identification of the Hazards of Materials for Emergency Response.

International Chemical Safety Cards(ICSC)(http://www.nihs.go.jp/ICSC) **3E Company/Ariel WebInsight DB**.

B. THE DATE OF PREPARATION OF THE MSDS : May 16, 2008

C. THE DATE OF PREPARATION OF THE LATEST REVISION

# January 2024

D. OTHER INFORMATIO:

The above information is believed to be correct but does not propose to be all inclusive and shall be used only as a guide. Sebang Global Battery CO.,Ltd. shall not be held liable for any damage resulting from handling or from contact with the above product. Each individual should make a determination as to the suitability of the information for their particular purpose(s). Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.